JRLite

Deliver What You Design

COVEFLEX BASS LONG

Indoor · Static White

Features

- Long max run length up to 20m (65.6ft) from single power feed
- IP20 rated, ideal for indoor non-condensing uses
- 5 years warranty

Date | Fixture type

Project name | Project phase

Applications

Under cabinets, coves, shelves, bedrooms, offices, hallways, etc.



Dimensions



Order Code (For LED tape)

Series	Environment	Voltage	CCT	Power
CFBASSL	**20**-Dry (IP20)	**24**-DC24V	**927**-RA90 2700K **930**-RA90 3000K **940**-RA90 4000K	**070**-7W/M

Assembly Builder

Left Feed Entry			
F	Front	**OW**	Open wire 15cm (5.9in.), 20 AWG
C	Closed	**MC**	Male connector with 20cm (0.66ft) cable, 20 AWG
		FC	Female connector with 20cm (0.66ft) cable, 20 AWG
		NA	Only for Closed Feed Entry

Assembly Builder

Right Feed Entry				Length	
F	Front	**OW**	Open wire 15cm (5.9in.), 20 AWG	**Max.**	20m (65.6ft)
C	Closed	**MC**	Male connector with 20cm (0.66ft) cable, 20 AWG		
		FC	Female connector with 20cm (0.66ft) cable, 20 AWG	**Increment**	50mm(1.97in.)
		NA	Only for Closed Feed Entry		

*For customizations, please inquire.

Profile Order Code

Product Code	Colors	Lens	Lengths
Please select on the Profile Compatibility page	**S** = Silver anodized	**OP** - Opal **FR** - Frosted* **CL** - Clear*	**1m**(3.28ft) **2m**(6.56ft)

*For custom RAL colors, please inquire.

*Profiles are sold separately. Refer to corresponding spec sheets for ordering info on profiles and their accessories (endcaps, mounting brackets, etc.)

*MOQ applies to Frosted (FR)and Clear (CL) lenses. Please inquire for details.

Lumen Output (lm/m)

Temp./Color	7W/M
2700K	525
3000K	595
4000K	630
Max. Run Length(M)	20

Technical Details	
Width	10mm (0.39in.)
LED Quantity	360 LEDs/Mt (7 LEDs/ft)
Beam Angle	180°
Efficacy	85lm/W @3000K 7W
CRI	Ra≥90
LED MacAdam	3 steps
Average Life (L70)	> 54,000 hours
Max. Length Per Reel	30m (98.4ft)
Storage Temperature	-25℃~ 60℃
Ambient Temperature	-25℃~ 45℃

Feed Entry Options

F: Front



C: Closed



Connector Wire Options

OW: Open wire, **Dry only**
Standard 15cm(0.59in.), 20 AWG (wire length customizable)



MC: Male connector, **Dry**, Standard 20cm(0.66ft), 20 AWG



FC: Female connector, **Dry**, Standard 20cm(0.66ft), 20 AWG

COVEFLEX BASS LONG

Indoor · Static White

Profile Compatibility

* Non-standard option, please contact us for customization support.


Lens Type & Light Transmission

CL Clear FR Frosted OP Opal

Surface


AP-1202

CL 52% FR 47% OP 39%




AP-1302

CL 70% FR 64% OP 52%




AP-1919

CL 64% FR 59% OP 48%




AP-2020

CL 64% FR 58% OP 48



AP-2601


CL 70% FR 64% OP 52%



Mud-In


AP-5615

CL 48% FR 44% OP 36%



AP-7615

CL 60% FR 55% OP 45%



Specification subject to change without notice.


COVEFLEX BASS LONG

Indoor · Static White

Recessed


AP-1201

CL 56% FR 51% OP 46%




AP-1207

CL 34% FR 31% OP 26%




AP-2015

CL 45% FR 41% OP 33%




AP-5035

CL 43% FR 40% OP 32%



AP-6575


CL 55% FR 50% OP 41%



Corner


AP-1001

CL 75% FR 69% OP 56%




AP-1002

CL 76% FR 69% OP 56%



AP-1101


CL 44% FR 40% OP 33%



Suspended


AP-5075

CL 54% FR 50% OP 41%




AP-60

CL 81% FR 74% OP 61%



AP-3535

CL 45% FR 41% OP 33%



COVEFLEX BASS LONG

Indoor · Static White

Connectors & Additional Accessories (Optional, purchase for extra)

CFS-STCN-2P-10
Strip to cable connector without wire, for 10mm (0.39in.) tape, 2 pin



CFS-STC-2P-10
Strip to cable connector with 15cm (5.91in) wire, for 10mm(0.39in.) tape, 2 pin



CFS-STSJ-2P-10
Strip to strip jumper connector with 15cm(5.91in.) wire, for 10mm (0.39in.) tape, 2 pin



AD00C-2-B
Strip to cable with black male & female connector, for 10mm (0.39in.) tape, 2 pin



AD00C-2-W
Strip to cable with white male & female connector, for 10mm (0.39in.) tape, 2 pin

CFS-STS-2P-10
Strip to strip connector, for 10mm (0.39in.) tape, 2 pin



CF-LC-2P-10
L-shaped corner connector, for 10mm (0.39in.) tape, 2 pin



CF-RC-2P-10
R-shaped corner connector, for 10mm (0.39in.) tape, 2 pin



AD00J-2-MC
Male SM connector with 20cm(0.66ft) cable, 2pin, IP20,Dry, 20AWG



AD00J-2-FC
Female SM connector with 20cm(0.66ft) cable, 2pin, IP20, Dry, 20AWG



VHB
VHB 3M adhesive back tape, stronger stickiness

COVEFLEX BASS LONG

Indoor · Static White

Drivers

Non-dimmable

Code	Max Load	Input	Output	Environment	Size (L x W x H)
XLG-150-24-A	150W	100-305VAC	24V	Dry/Damp/IP67	180 * 63 * 35.5 mm
LPV-150-24	150W	180-305VAC		Dry/Damp/IP67	148 * 40 * 30 mm
LRS-150-24	150W	85-132VAC / 170-264VAC		Dry	99 * 97 * 30 mm

3 in 1-dimmable


Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24B-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm
PWM-120-24	120W	90-305VAC / 127-431VDC		Dry/Damp/IP67	191 * 63 * 37.5 mm

DALI-dimmable

Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24DA-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm

Wiring Diagram


Non-dimmable



3 in 1-dimmable



DALI-dimmable



Specification subject to change without notice.

COVEFLEX BASS LONG

Indoor · Static White

24V Voltage Drop & Maximum Wire Length Chart

Based on 24V voltage with a 3% voltage drop allowance. Indicates the maximum wire length from the power supply to the start of the run.

Total load	8AWG	10AWG	12AWG	14AWG	16AWG	18AWG	20AWG	22AWG
10W / 0.4A	484.0m	304.5m	191.4m	120.4m	75.5m	47.5m	29.8m	18.5m
20W / 0.8A	242.0m	152.1m	95.7m	60.0m	37.8m	23.7m	14.9m	9.1m
30W / 1.3A	161.2m	101.5m	63.7m	39.9m	24.9m	15.8m	9.7m	6.1m
40W / 1.7A	121.0m	75.9m	47.8m	29.8m	18.9m	11.8m	7.3m	4.5m
50W / 2.1A	96.6m	60.6m	38.1m	24.0m	14.9m	9.4m	5.7m	3.6m
60W / 2.5A	80.4m	50.6m	31.7m	19.8m	12.5m	7.9m	4.8m	3.0m
70W / 2.9A	68.8m	43.2m	27.1m	17.0m	10.6m	6.7m	4.2m	2.4m
80W / 3.3A	60.3m	37.8m	23.7m	14.9m	9.4m	5.7m	3.6m	2.1m
90W / 3.8A	53.6m	33.8m	21.0m	13.1m	8.2m	5.1m	3.0m	1.8m
100W / 4.2A	48.1m	30.1m	18.9m	11.8m	7.3m	4.5m	2.7m	1.8m
110W / 4.6A	43.8m	27.4m	17.3m	10.6m	6.7m	4.2m	2.7m	1.5m
120W / 5.0A	40.2m	25.3m	15.8m	9.7m	6.1m	3.9m	2.4m	1.5m
130W / 5.4A	37.1m	23.1m	14.6m	9.1m	5.7m	3.6m	2.1m	1.2m
140W / 5.8A	34.4m	21.6m	13.4m	8.5m	5.1m	3.3m	2.1m	1.2m
150W / 6.3A	32.0m	20.1m	12.5m	7.9m	4.8m	3.0m	1.8m	1.2m
160W / 6.7A	30.1m	18.9m	11.8m	7.3m	4.5m	2.7m	1.8m	0.9m
170W / 7.1A	28.3m	17.6m	10.9m	7.0m	4.2m	2.7m	1.5m	0.9m
180W / 7.5A	26.8m	16.7m	10.3m	6.7m	3.9m	2.4m	1.5m	0.9m
190W / 7.9A	25.3m	15.8m	10.0m	6.0m	3.9m	2.4m	1.5m	0.9m
200W / 8.3A	24.0m	14.9m	9.4m	5.7m	3.6m	2.1m	1.2m	0.9m
210W / 8.8A	22.8m	14.3m	8.8m	5.4m	3.3m	2.1m	1.2m	0.6m
220W / 9.2A	21.9m	13.7m	8.5m	5.4m	3.3m	2.1m	1.2m	0.6m
230W / 9.6A	21.0m	13.1m	8.2m	5.1m	3.0m	1.8m	1.2m	0.6m
240W / 10.0A	20.1m	12.5m	7.9m	4.8m	3.0m	1.8m	1.2m	0.6m
250W / 10.4A	19.2m	12.1m	7.6m	4.5m	2.7m	1.8m	0.9m	0.6m