LEDLINE AXE 1617 RGBW

3D Bending · RGBW

Features

• Smooth surface with cutting mark without seeing PCB and support reminding wrong bending
• IP68 protection(not for underwater application), UV resistance,and chemical resistance ensure the durability in various environments.
• Contains 84 LEDs per meter, with a minimum cutting unit of 71.43mm, and supports a maximum single-feed run length of up to 8 meters.
• 3 years warranty

Date

Fixture type

Project name


Project phase



Applications

Living rooms, TV walls, feature walls, under-cabinet areas, staircases, ceiling coves, hallways, etc.

Bending Directions & Diameters



Order Code

Model	Bend Direction	Voltage	CCT	Power
AXE1617	**3D**-3D bending	**24V**-DC24V	**RGBW827**-RGBW(RA80 2700K) **RGBW830**-RGBW(RA80 3000K)	**135**-13.5W/M

Assembly Builder

Left Feed Entry			
F	Front	**OW**	Open wire 30cm(0.98ft)
B	Bottom	**MC**	Male connector with 30cm(0.98ft) cable
S	Side	**FC**	Female connector with 30cm(0.98ft)cable
C	Closed	**NA**	Only for Closed Feed Entry

Assembly Builder

Right Feed Entry			
F	Front	**OW**	Open wire 30cm(0.98ft)
B	Bottom	**MC**	Male connector with 30cm(0.98ft) cable
S	Side	**FC**	Female connector with 30cm(0.98ft)cable
C	Closed	**NA**	Only for Closed Feed Entry

Length	
Max. nominal	8m(26.25ft)
Increment	71.43mm (2.81in.)

Mounting Order Code

Product Code
Please select on the Mounting Options page

*We will list the nearest actual manufacturing length on the quotation, based on your requested length.

LEDLINE AXE 1617 RGBW

Lumen Output (lm/m)

CCT	13.5W/M
R	31
G	107
B	21
W27K	95
W30K	97
RGBW30K	253
Max. Run Length	8m


Techinical Details

Efficacy	18.7lm/W @RGBW30K 13.5W
CRI	Ra≥80
Beam Angle	110°
Average Life (L70B10)	>32,000 hours
Storage Temperature	-25℃~ 60℃
Operating Temperature	-25℃~ 60℃

Photometry

AXE16173D-24-RGBW830-135

LEDLINE AXE 1617, 3D bending, 24V, RGBW(RA80, 3000K), 13.5W/M




Zonal Lumen Summary


Zone	Lumen	% Fixture
0-30	65.81	25.9%
0-40	107.7	42.5%
0-60	190.8	75.2%
0-90	249.6	98.4%
0-180	253.6	100.0%

LEDLINE AXE 1617 RGBW


Feed Entry / End Cap Options


FT: Flush Translucent – IP68, factory-made only





Silicone end cap – IP67, for field cuttable only







Connector Wire Options



OW: Open wire, **Dry only**
Standard 30cm(0.98ft),20 AWG,
wire length customizable





MC: Male connector, **Wet**
Standard 30cm(0.98ft), 20 AWG



FC: Female connector, **Wet**
Standard 30cm(0.98ft), 20 AWG



Mounting Options



AC167-AP


Name	Straight surface profile
Material	Aluminum
Standard Length	1M (3.28ft)




AC167-CR


Name	Bendable surface profile
Material	Aluminum
Standard Length	1M (3.28ft)
Min. Bending Diameter	600mm(23.6in.)



AC167-EP



Name	Straight recessed profile
Material	Aluminum
Standard Length	1M (3.28ft)



AC167-LP


Name	Mud-in profile
Material	Aluminum
Standard Length	1M (3.28ft)




AC167-SCRL


Name	Bendable mud-in profile
Material	Aluminum
Standard Length	1M (3.28ft)
Min. Bending Diameter	600mm(23.6in.)



AC167-SGP


Name	Straight surface profile
Material	Aluminum with silicone groove
Standard Length	1M (3.28ft)



AC167-CSGP

Name	Bendable surface profile
Material	Aluminum with silicone groove
Standard Length	1M (3.28ft)
Min. Bending Diameter	600mm(23.6in.) only side bend




AC167-BA

Name	Light-block profile
Material	Aluminum
Standard Length	1M (3.28ft)

LEDLINE AXE 1617 RGBW

3D Bending · RGBW








AC167-PC

Name	PC profile
Material	Polycarbonate
Standard Length	1M (3.28ft)










AC167-CPC

Name	Bendable PC profile
Material	Polycarbonate
Standard Length	1M (3.28ft)
Min. Bending Diameter	300mm(11.81in.)

Clip Options








AC167-MC

Name	Mounting clip
Material	Aluminum
Standard Length	25mm (0.98in.)

Bracket Options










AC167-SET-LA

Name	L-shaped mounting bracket
Material	Aluminum
Standard Length	20mm(0.79in.)

* AC167-SET-LA must be installed with AC167-AP











AC167-AMB

Name	Adjustable mounting clip
Material	Stainless steel
Standard Length	25.5mm (1 in.)

* AC167-AMB must be installed with AC167-AP










AC167-SET-LC

Name	Spring clip
Standard Pkg	1pcs

* AC167-SET-LC must be installed with AC167-EP

Tool Options



IF-167


Name	Fixture
Material	Resin
Standard Pkg	1pcs

* Insertion Fixture for AC167-CPC


LEDLINE AXE 1617 RGBW

3D Bending · RGBW


Silicone End Caps (Optional, purchase for extra)



AC167-EC
Silicone closed end cap



AC167-EC5-F
Silicone end cap front entry with 30cm(0.98ft) cable, 2 pin



AC167-EC5-S
Silicone end cap side entry with 30cm(0.98ft) cable, 2 pin



AC167-EC5-B
Silicone end cap bottom entry with 30cm(0.98ft) cable, 2 pin

Additional Accessories (Optional, purchase for extra)



AD007-5-MCW
Male connector,
30cm (0.98ft) UL white cable,
5 pin, IP67, Wet, 20 AWG



AD007-5-FCW
Female connector,
30cm (0.98ft) UL white cable,
5 pin, IP67, Wet, 20 AWG



AD007-5-MCB
Male connector,
30cm (0.98ft) black cable,
5 pin, IP67, Wet, 20 AWG



AD007-5-FCB
Female connector,
30cm (0.98ft) black cable,
5 pin, IP67, Wet, 20 AWG



AF001-1
1 Adjustable angle scissors set,
with 4 spare blades

LEDLINE AXE 1617 RGBW

3D Bending · RGBW

Drivers


Non-dimmable


Code	Max Load	Input	Output	Environment	Size (L x W x H)
ELG-150-24A-3Y	150W	100-305VAC	24V	Dry/Damp/IP67	219 * 63 * 35.5 mm
LRS-150-24	150W	85-132VAC / 170-264VAC	24V	Dry	149 * 97 * 30 mm

DMX-Decoders & Controllers Options

Type	Code	Description	Environment	Size (L x W x H)
DMX Decoders	D4-F	4 channels output, Max. 5A current per channel, up to 480W output power	Indoor	175 * 42 * 33 mm
Controllers	EX4S	512 DMX channels	Indoor	86 * 86 * 36 mm
Power Repeaters	LT-3040-5A	4 channels output, Max. 5A current per channel, up to 480W output power	Indoor	175 * 44 * 30 mm
Signal Amplifier	LT-123	DMX(485) signal amplifier, 1 input / 3 outputs	Indoor	192 * 80 * 41 mm

Wiring Diagram





LEDLINE AXE 1617 RGBW

24V Voltage Drop & Maximum Wire Length Chart

Based on 24V voltage with a 3% voltage drop allowance. Indicates the maximum wire length from the power supply to the start of the run.

Total load	8AWG	10AWG	12AWG	14AWG	16AWG	18AWG	20AWG	22AWG
10W / 0.4A	484.0m	304.5m	191.4m	120.4m	75.5m	47.5m	29.8m	18.5m
20W / 0.8A	242.0m	152.1m	95.7m	60.0m	37.8m	23.7m	14.9m	9.1m
30W / 1.3A	161.2m	101.5m	63.7m	39.9m	24.9m	15.8m	9.7m	6.1m
40W / 1.7A	121.0m	75.9m	47.8m	29.8m	18.9m	11.8m	7.3m	4.5m
50W / 2.1A	96.6m	60.6m	38.1m	24.0m	14.9m	9.4m	5.7m	3.6m
60W / 2.5A	80.4m	50.6m	31.7m	19.8m	12.5m	7.9m	4.8m	3.0m
70W / 2.9A	68.8m	43.2m	27.1m	17.0m	10.6m	6.7m	4.2m	2.4m
80W / 3.3A	60.3m	37.8m	23.7m	14.9m	9.4m	5.7m	3.6m	2.1m
90W / 3.8A	53.6m	33.8m	21.0m	13.1m	8.2m	5.1m	3.0m	1.8m
100W / 4.2A	48.1m	30.1m	18.9m	11.8m	7.3m	4.5m	2.7m	1.8m
110W / 4.6A	43.8m	27.4m	17.3m	10.6m	6.7m	4.2m	2.7m	1.5m
120W / 5.0A	40.2m	25.3m	15.8m	9.7m	6.1m	3.9m	2.4m	1.5m
130W / 5.4A	37.1m	23.1m	14.6m	9.1m	5.7m	3.6m	2.1m	1.2m
140W / 5.8A	34.4m	21.6m	13.4m	8.5m	5.1m	3.3m	2.1m	1.2m
150W / 6.3A	32.0m	20.1m	12.5m	7.9m	4.8m	3.0m	1.8m	1.2m
160W / 6.7A	30.1m	18.9m	11.8m	7.3m	4.5m	2.7m	1.8m	0.9m
170W / 7.1A	28.3m	17.6m	10.9m	7.0m	4.2m	2.7m	1.5m	0.9m
180W / 7.5A	26.8m	16.7m	10.3m	6.7m	3.9m	2.4m	1.5m	0.9m
190W / 7.9A	25.3m	15.8m	10.0m	6.0m	3.9m	2.4m	1.5m	0.9m
200W / 8.3A	24.0m	14.9m	9.4m	5.7m	3.6m	2.1m	1.2m	0.9m
210W / 8.8A	22.8m	14.3m	8.8m	5.4m	3.3m	2.1m	1.2m	0.6m
220W / 9.2A	21.9m	13.7m	8.5m	5.4m	3.3m	2.1m	1.2m	0.6m
230W / 9.6A	21.0m	13.1m	8.2m	5.1m	3.0m	1.8m	1.2m	0.6m
240W / 10.0A	20.1m	12.5m	7.9m	4.8m	3.0m	1.8m	1.2m	0.6m
250W / 10.4A	19.2m	12.1m	7.6m	4.5m	2.7m	1.8m	0.9m	0.6m